



| NO. | 定义    | NO. | 定义     |
|-----|-------|-----|--------|
| 1   | LEDA  | 26  | G1     |
| 2   | LEDA  | 27  | G0     |
| 3   | LEDK  | 28  | R7     |
| 4   | LEDK  | 29  | R6     |
| 5   | GND   | 30  | R5     |
| 6   | VOCM  | 31  | R4     |
| 7   | DVDD  | 32  | R3     |
| 8   | MODE  | 33  | R2     |
| 9   | DE    | 34  | R1     |
| 10  | VCYNC | 35  | R0     |
| 11  | HSYNC | 36  | GND    |
| 12  | B7    | 37  | DCLK   |
| 13  | B6    | 38  | GND    |
| 14  | B5    | 39  | L/R    |
| 15  | B4    | 40  | U/D    |
| 16  | B3    | 41  | VGH    |
| 17  | B2    | 42  | VGL    |
| 18  | B1    | 43  | AVDD   |
| 19  | B0    | 44  | RESET  |
| 20  | G7    | 45  | NC     |
| 21  | G6    | 46  | VCOM   |
| 22  | G5    | 47  | DITHER |
| 23  | G4    | 48  | GND    |
| 24  | G3    | 49  | NC     |
| 25  | G2    | 50  | NC     |



7" TFT Display  
 450cd/m<sup>2</sup>  
 800xRGBx480  
 164.9(W)100(H)5.7(D)mm  
 Opt. Temp. Range: -10°C +70°C  
 View Angle: 70/70/50/60 6:00 O'clock  
 RoHS Compliant  
 TTL

# YLT070PHT50AE-H3