



PIN	Function
1	LEDA
2	LEDA
3	LEDA
4	NC
5	LEDK
6	LEDK
7	LEDK
8	LEDK
9	GND
10	GND
11	MIPI_D2+ HSSI_D2_P
12	MIPI_D2- HSSI_D2_N
13	GND
14	MIPI_D1+ HSSI_D1_P
15	MIPI_D1- HSSI_D1_N
16	GND Ground.
17	MIPI_CLK+ HSSI_CLK_P
18	MIPI_CLK- HSSI_CLK_N
19	GND Ground.
20	MIPI_D0+ HSSI_D0_P
21	MIPI_D0- HSSI_D0_N
22	GND Ground.
23	MIPI_D3+ HSSI_D3_P
24	MIPI_D3- HSSI_D3_N
25	GND Ground.
26	LCD_ID
27	RESET
28	NC
29	IO/VCC 1.8V
30	VCI 3.0-3.6V
31	VCI 3.0-3.6V

8" TFT Display
350cd/m²
800xRGBx1280
114.7(W)184.2(H)2.6(D)mm
Opt. Temp. Range: -10°C +50°C
View Angle: 85/85/85/85 IPS (All)
RoHS Compliant
MIPI



DETAIL A SC (3:1)

FP270H-031G1AM (H=1mm)



CURRENT IF=160mA
 3C*8B=24LED

YLT080SXM31AA-A7-SX