



Pin NO.	Symbol	Input/Out put	Description
1	VDD	I	SUPPLY LOGIC VOLTAGE (5.0V)
2	VSS	I	POWER Ground
3	VOUT	O	BOOSTER OUTPUT TERMINAL
4	V0	I	POWER SUPPLY FOR LCD DRIVER
5	FLM	I	Scan start pulse
6	CL 1	I	Dot data latch pulse
7	CL 2	I	Dot data shift clock for X driver
8	M	I	Frame signal
9	/DISPOFF	I	Power down signal when display OFF
10~13	DB 0~DB 3	I/O	Dot data output bus to X driver
14	K	I	BACKLIGHT NEGATIVE
15	AW	I	BACKLIGHT WHITE POSITIVE (3.3V)
16	AB	I	BACKLIGHT BLUE POSITIVE (3.3V)
17	AG	I	BACKLIGHT GREEN POSITIVE (3.3V)
18	NC		NO CONNECTION

All rights strictly reserved.
Reproduction or issue to third parties in any form whatever
is not permitted without written authority from the proprietor.

P/N: YMF-G480240A

sales@yaoyulcd.com
www.yaoyulcd.com
0762-6686756

ISO9001 - CN17/30422
ISO14001 - CN17/30423
IATF16949 - CN17/30525