



1	VSS
2	VDD
3	XCS
4	SCL
5	SI
6	IF3
7	IF2
8	IF1
9	RST
10	E_RD
11	DB15
12	DB14
13	DB13
14	DB12
15	DB11
16	DB10
17	DB9
18	DB8
19	DB7
20	DB6
21	DB5
22	DB4
23	DB3
24	DB2
25	DB1
26	DB0
27	RW_WR
28	A0

- |                           |                        |
|---------------------------|------------------------|
| 1. DISPLAY TYPE:          | FSTN                   |
| 2. VIEWING DIRECTION:     | 6:00                   |
| 3. POLARIZER MODE:        | TRANSFLECTIVE/POSITIVE |
| 4. OPERATING TEMP:        | -20°C~+70°C            |
| 5. STORAGE TEMP:          | -30°C~+80°C            |
| 6. LOGIC VOLTAGE:         | 3V~3.3V                |
| 7. LCD OPERATION VOLTAGE: | 17.5V                  |
| 8. DRIVE METHOD:          | 1/160DUTY 1/13BIAS     |
| 9. DRIVER IC:             | ST7529                 |
| 10. BACKLIGHT:            | LED(WHITE)             |

P/N: YMSC-G160160C

sales@yaoyulcd.com  
www.yaoyulcd.com  
0762-6686756

ISO9001 - CN17/30422  
ISO14001 - CN17/30423  
IATF16949 - CN17/30525