



NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
- 4.OPERATING TEMP: -20°C ~ +70°C
- 5.STORAGE TEMP: -30°C ~ +80°C
- 6.LOGIC VOLTAGE: VDD=5.0V
- 7.LCD DRIVER VOLTAGE: Vop=18.5V
- 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 9.DRIVE IC: T6963C
- 10.BACKLIGHT TYPE: WHITE LED BACKLIGHT

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
FG	VSS	VDD	V0	/WR	/RD	/CE	C/D	NC	/RST	DB0	DB1	DB2	DB3	DB4	DB5	DB6
18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
DB7	FS	NC	A	K	ED	CDATA	FR	LP	CP	NC	VDD	VSS	V0	VEE	A	K

P/N: YMSP-G240128A

sales@yaoyulcd.com  
www.yaoyulcd.com  
0762-6686756

ISO9001 - CN17/30422  
ISO14001 - CN17/30423  
IATF16949 - CN17/30525