



NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING ANGLE: 6:00
- 3.POLARIZER MODE: TRANFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C~~+70°C
- 5.STORAGE TEMP: -30°C~~+80°C
- 6.LOGIC VOLTAGE: VDD=5.0V
- 7.LCD DRIVER VOLTAGE: Vop=16.5V
- 8.DRIVE METHOD: 1/128DUTY,1/12BIAS
- 9.DRIVE IC: T6963C
- 10.BACKLIGHT TYPE: LED(YELLOW-GREEN,4.2VDC)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VSS	VDD	V0	C/D	RD	WR	D0	D1	D2	D3	D4	D5	D6	D7	CE	RST	VOUT	FS	EL1	EL2

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor.

P/N: YMSP-G240128D

sales@yaoyulcd.com
www.yaoyulcd.com
0762-6686756

ISO9001 - CN17/30422
ISO14001 - CN17/30423
IATF16949 - CN17/30525